

PRODUCT FEATURES



LAMPING

Hand-bendable, field-cuttable MonoRail is rated for 300 watts at 12 volts, 600 watts at 24 volts. Each piece of rail is shipped with conductive connectors to join rail pieces end to end. Order additional connectors if cutting and rejoining rails. Standard

Satin Nickel/Clear



Antique
Bronze/Brown

Satin Nickel/Clear

ORDERING INFORMATION

700MOA	SHAPE OR SIZE	LENGTH (A)	COLOR	FINISH
	STRAIGHT	24 24"	BR BROWN	Z ANTIQUE BRONZE
		48 48"	CLEAR	S SATIN NICKEL
		96 96"		

700MOA

JOB NAME

NOTES

SPECIFICATIONS

PRIMARY MATERIAL

SHADE MATERIAL

NET WEIGHT 0.27 lbs

HEIGHT 0.6in

WIDTH 0.3in

LENGTH 24in


WET LISTED

DAMP LISTED

DRY LISTED

GENERAL LISTING ETL Listed

INCLUDES



LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS				
WATTS				
MAX WATTAGE PER BULB				
CCT				
CRI				
LED LIFETIME				
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE				
LAMP SHAPE				
LAMP INCLUDED?				
WARRANTY**			1 Year	

* Dimming information available at www.techlighting.com/Downloads#dimming** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 / JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8.			N/A
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.			N/A

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

