

MONORAIL END POWER FEED

VISUAL COMFORT & CO.

PRODUCT FEATURES

LAMPING

The end power feed pushes into an end of the MonoRail and includes a removable 4" round canopy and 12' of field-cutable softwire leads.



MonoRail End Power Feed



MonoRail End Power Feed

ORDERING INFORMATION

700MOPEND SHAPE OR SIZE	FINISH
4" ROUND END POWER FEED	Z ANTIQUE BRONZE
	S SATIN NICKEL

700MOPEND

JOB NAME


NOTES

MONORAIL END POWER FEED

VISUAL COMFORT & CO.

SPECIFICATIONS

PRIMARY MATERIAL	
SHADE MATERIAL	
NET WEIGHT	1 lbs
HEIGHT	4in
WIDTH	4in
LENGTH	4in
WET LISTED	
DAMP LISTED	
DRY LISTED	
GENERAL LISTING	ETL Listed
INCLUDES	



LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS				
WATTS				
MAX WATTAGE PER BULB				
CCT				
CRI				
LED LIFETIME				
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE				
LAMP SHAPE				
LAMP INCLUDED?				
WARRANTY**			1 Year	

* Dimming information available at www.techlighting.com/Downloads#dimming

** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 / JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8.			N/A
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.			N/A

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

