

POWER SUPPLY 0-10V REMOTE 24VDC 5 PERCENT


VISUAL COMFORT & CO.

PRODUCT FEATURES

Remote Power Supply for 0-10V dimming down to 5%. Universal input 120V-277V with 24V DC output available in 60W and 96W. Enclosure included.



LAMPING



ORDERING INFORMATION

ESPR	WATTAGE	OUTPUT VOLTAGE	CONTROLS	INPUT VOLTAGE
	060 60W	24 24VDC	010 0-10V	120-277 120-277V
	100 100W			

ESPR

JOB NAME


NOTES

POWER SUPPLY 0-10V REMOTE 24VDC 5 PERCENT

VISUAL COMFORT & Co.

SPECIFICATIONS

PRIMARY MATERIAL
SHADE MATERIAL
NET WEIGHT
HEIGHT
WIDTH
LENGTH
WET LISTED
DAMP LISTED
DRY LISTED
GENERAL LISTING
INCLUDES



LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS				
WATTS				
MAX WATTAGE PER BULB				
CCT				
CRI				
LED LIFETIME				
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE				
LAMP SHAPE				
LAMP INCLUDED?				
WARRANTY**				

* Dimming information available at www.techlighting.com/Downloads#dimming
** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 / JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8.			Yes
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.			Yes

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.