

LUTRON HI-LUME ECOSYSTEM/3-WIRE 0.1
PERCENT

VISUAL COMFORT & CO.

PRODUCT FEATURES

Remote Lutron Hi-lume Power Supply for EcoSystem compatibility with dimming down to 0.1%. Universal input 120V-277V with 24V DC output available in 100W. Enclosure included.



LAMPING

Closed



Closed

Open

ORDERING INFORMATION

ESPR	WATTAGE	OUTPUT VOLTAGE	CONTROLS	INPUT VOLTAGE
	100100W	24 24VDC	HLECO HI-LUME 3 WIRE/ECO-SYSTEM	120-277 120-277V

ESPR

JOB NAME

NOTES

LUTRON HI-LUME ECOSYSTEM/3-WIRE 0.1 PERCENT

VISUAL COMFORT & Co.

SPECIFICATIONS

PRIMARY MATERIAL
SHADE MATERIAL
NET WEIGHT
HEIGHT
WIDTH
LENGTH
WET LISTED
DAMP LISTED
DRY LISTED
GENERAL LISTING
INCLUDES



LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS				
WATTS				
MAX WATTAGE PER BULB				
CCT				
CRI				
LED LIFETIME				
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE				
LAMP SHAPE				
LAMP INCLUDED?				
WARRANTY**				

* Dimming information available at www.techlighting.com/Downloads#dimming
** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 / JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8.			Yes
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.			Yes

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.