


PRODUCT FEATURES

LAMPING

All dual-feed canopies and surface transformers are shipped with isolating connectors; order additional if required by layout. Pair.



Kable Lite Isolating Connectors



Kable Lite Isolating Connectors

ORDERING INFORMATION

700P	SHAPE OR SIZE	
	BARE CABLE	ARTD1
	INSULATED CABLE	RTD1L

700P

JOB NAME


NOTES

KABLE LITE ISOLATING CONNECTORS

VISUAL COMFORT & CO.

SPECIFICATIONS

PRIMARY MATERIAL	
SHADE MATERIAL	
NET WEIGHT	0.01 lbs
HEIGHT	0.3in
WIDTH	1in
LENGTH	3in
WET LISTED	
DAMP LISTED	
DRY LISTED	
GENERAL LISTING	ETL Listed
INCLUDES	



LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS				
WATTS				
MAX WATTAGE PER BULB				
CCT				
CRI				
LED LIFETIME				
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE				
LAMP SHAPE				
LAMP INCLUDED?				
WARRANTY**	1 Year			

* Dimming information available at www.techlighting.com/Downloads#dimming
** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 / JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8.			N/A
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.			N/A

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

