

GENERATION BRANDS, LLC TEST REPORT

SCOPE OF WORK

LED Performance Testing

MODEL NUMBER

ESSF0606P48150930FW1

PROJECT NUMBER

G104349704

REPORT NUMBER

104349704CHI-039

ISSUE DATE

11/16/2020

REVISED DATE

None

TEST DATES

11/03/2020 through 11/05/2020.

DOCUMENT CONTROL NUMBER

RTTDS-R-AMER-Test-3407

© 2017 INTERTEK



REPORT NUMBER

104349704CHI-039

MODEL NUMBER(s)

ESSF0606P48150930FW1

REPORT RENDERED TO:

GENERATION BRANDS, LLC
7400 LINDER AVE
SKOKIE, IL 60077
USA

STATEMENT OF LIMITATION

NVLAP Lab Code 600186-0. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

AUTHORIZATION

The testing performed was authorized by signed quote number Qu-01080748-3.

TEST STANDARDS

IESNA LM-79 - 2008: Electrical and Photometric Measurements of Solid State Lighting

ANSI NEMA ANSLG C78.377: 2017: Specifications for the Chromaticity of Solid State Lighting (SSL) Products

In Charge of Testing:



Ian Smith
Engineer
Lighting Division

Reviewer:



Jeff Davis
NA Technical Lead
Lighting Division

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

SAMPLE INFORMATION

REPORT NO. 104349704CHI-039

ITEMS RECEIVED

Item No.	Control No.	Model No.	Description	Type	Received
1	AH10292020032135	ESSF0606P48150930FW 1	ESSENCE 0606 P 200 930 FW	Production	10/29/2020

TESTED SAMPLE CONFIGURATIONS

Config No.	Tested Model No.	Item Nos. Utilized
1	ESSF0606P48150930FW1	1

SUMMARY

REPORT NO. 104349704CHI-039

PRODUCT INFORMATION AND SUMMARY OF DATA

Product Model No.:	ESSF0606P48150930FW1
Product Description:	ESSENCE 0606 P 200 930 FW
LED Model No.:	P Series 200lm/ft
Light Source:	LED

Criteria	Results	
	Goniophotometer	Integrating Sphere
Light Output (lumens)	665.2	669.6
Input Power (W) @ 24 (Vdc)	7.52	7.58
Lumen Efficacy (lm/W)	88.5	88.4

Criteria	Results
Input ATHD (%) @ 24 (Vdc)	NA
Correlated Color Temperature (K)	3007
Color Rendering Index - Ra (l)	97.7
Color Rendering Index - R9 (l)	97.6
Duv (l)	-0.0007
Chromaticity Coordinate (x)	0.435
Chromaticity Coordinate (y)	0.402
Chromaticity Coordinate (u')	0.251
Chromaticity Coordinate (v')	0.520

TEST METHODS

SEASONING IN SAMPLE ORIENTATION - LED PRODUCTS

No seasoning was performed in accordance with IESNA LM-79.

INTEGRATING SPHERE TESTING

A spectroradiometer and integrating sphere were used to measure the spectral distribution for each EUT resulting in photometric and colorimetric data. Electrical measurements of the unit were measured using a power analyzer. Each EUT was operated at the rated input voltage of the system in its designated orientation. The ambient temperature was measured at a position inside the sphere and stabilization procedures to LM-79 were followed.

TYPE C GONIOPHOTOMETER DISTRIBUTION TESTING

A Type C Mirror Goniophotometer system was used to measure the luminous intensity (candela) at each angle of distribution for the EUT. Electrical measurements of the unit were measured using a power analyzer. Each EUT was operated at the rated input voltage of the system in its designated orientation. The ambient temperature was measured at a position near the EUT at equal height and stabilization procedures to LM-79 were followed.

TYPE C GONIOPHOTOMETER DISTRIBUTION TESTING

REPORT NO. 104349704CHI-039

Test Configuration	Tested Model No.	Pass/Fail/NA
1	ESSF0606P48150930FW1	NA

PHOTOMETRIC AND ELECTRICAL MEASUREMENTS (25°C +/- 1°C)


Base Orientation	Input Voltage (Vdc)	Input Current (mA)	Input Power (W)	Input Power Factor ()
Up	24.0	313.5	7.52	NA

Light Output (lm)	Lumen Efficacy (lm/W)
665.2	88.5

INTENSITY SUMMARY - CANDELA


Angle	0	22.5	45	67.5	90
0	293	293	293	293	293
5	286	288	290	294	298
10	282	284	285	288	290
15	276	275	274	274	276
20	266	263	259	256	257
25	253	247	240	234	233
30	236	228	218	210	208
35	216	206	196	184	182
40	194	183	171	159	156
45	172	160	147	135	134
50	148	137	124	114	112
55	125	114	103	95	93
60	102	92	83	77	76
65	81	73	66	60	59
70	60	54	49	46	45
75	41	36	34	32	31
80	24	21	21	20	20
85	10	9	11	11	11
90	0	0	0	0	0
95	0	0	0	0	0
100	0	0	0	0	0
105	0	0	0	0	0
110	0	0	0	0	0
115	0	0	0	0	0
120	0	0	0	0	0
125	0	0	0	0	0
130	0	0	0	0	0
135	0	0	0	0	0
140	0	0	0	0	0
145	0	0	0	0	0
150	0	0	0	0	0
155	0	0	0	0	0
160	0	0	0	0	0
165	0	0	0	0	0
170	0	0	0	0	0
175	0	0	0	0	0
180	0	0	0	0	0

Entire luminous intensity matrix found in .IES file



REPORT NO. 104349704CHI-039

ILLUMINANCE SUMMARY



ZONAL LUMENS

Zonal Lumen Summary					
Zone	Lumens	Luminaire	Zone	Lumens	Total
0-30	215.8	32.4%	90-100	0.0	0.0%
0-40	338.5	50.9%	100-110	0.0	0.0%
0-60	548.1	82.4%	110-120	0.0	0.0%
60-90	117.1	17.6%	120-130	0.0	0.0%
70-100	49.7	7.5%	130-140	0.0	0.0%
90-120	0.0	0.0%	140-150	0.0	0.0%
0-90	665.2	100.0%	150-160	0.0	0.0%
90-180	0.0	0.0%	160-170	0.0	0.0%
0-180	665.2	100.0%	170-180	0.0	0.0%

INTEGRATING SPHERE TESTING

REPORT NO. 104349704CHI-039

Test Configuration	Tested Model No.	Pass/Fail/NA
1	ESSF0606P48150930FW1	NA

PHOTOMETRIC, COLORIMETRIC, AND ELECTRICAL MEASUREMENTS (25°C +/- 1°C)


Base Orientation
Up

Input Voltage (Vdc)	Input Current (mA)	Input Power (W)	Input Power Factor ()	Input ATHD (%)
24.01	315.6	7.58	NA	NA

Measured at 24.01(Vdc)

Light Output (lm)	Lumen Efficacy (lm/W)	CCT (K)	CRI - Ra ()	CRI - R9 ()
669.6	88.4	3007	97.7	97.6

Duv ()	1931 Chrom (x)	1931 Chrom (y)	1976 Chrom (u')	1976 Chrom (v')
-0.0007	0.435	0.402	0.251	0.520




REPORT NO. 104349704CHI-039

SPECTRAL DISTRIBUTION OVER WAVELENGTHS

nm	mW/nm		nm	mW/nm		nm	mW/nm		nm	mW/nm
350	0.0		460	5.1		570	9.3		680	9.3
355	0.2		465	5.0		575	9.4		685	8.5
360	0.1		470	4.3		580	9.6		690	7.6
365	0.1		475	3.5		585	9.9		695	6.7
370	0.0		480	3.6		590	10.3		700	6.1
375	0.1		485	3.9		595	10.8		705	5.2
380	0.0		490	4.2		600	11.3		710	4.6
385	0.0		495	4.8		605	11.9		715	4.0
390	0.1		500	5.4		610	12.6		720	3.5
395	0.0		505	5.9		615	13.2		725	3.1
400	0.1		510	6.4		620	13.7		730	2.6
405	0.1		515	6.8		625	14.3		735	2.3
410	0.1		520	7.2		630	14.6		740	1.9
415	0.1		525	7.5		635	14.7		745	1.7
420	0.2		530	7.8		640	14.7		750	1.4
425	0.3		535	8.1		645	14.5		755	1.2
430	0.5		540	8.4		650	14.1		760	1.0
435	0.9		545	8.6		655	13.5		765	0.8
440	1.9		550	8.8		660	12.8		770	0.8
445	4.2		555	8.9		665	12.1		775	0.7
450	7.4		560	9.1		670	11.2		780	0.5
455	6.9		565	9.2		675	10.3		---	---

Without correction of sample absorption.



Portrayed color in graphic is estimated by wavelength (nm) and may not be exact - it is a visual representation only

EQUIPMENT LIST

REPORT NO. 104349704CHI-039

#	Equipment	Model No	Control No.	Last Cal	Cal Due
1	Yokogawa Power Meter	WT210	146919	7/1/2020	7/1/2021
2	Omega Thermometer	DPI8-C24	146920	10/1/2020	10/1/2021
3	LSI High Speed Mirror Goniometer	6440T	146928	VBV	VBV
4	Newport Thermohygrometer	iServer	146957	12/2/2019	12/2/2020
5	Sorenson DC Power Supply	XHR 150-7	146922	VBV	VBV
6	Labsphere Spectroradiometer	CDS-600	146923	VBV	VBV
7	2M Rotating Sphere	7660-ROT	146923	VBV	VBV
8	Omega thermometer	USB TC08	EQA002615	4/7/2020	4/7/2021
9	Ametek DC Power Supply	XFR150-8	1468464	VBV	VBV
10	Yokogawa Power Meter	WT210	146880	10/1/2020	10/1/2021
11	Chroma Power Supply	61604	CHI0371	VBV	VBV
12					
13					
14					
15					
16					
17					
18					
19					
20					
21					
22					
23					
24					
25					
26					
27					
28					
29					
30					

Note: Standard sources listed above are traceable to NIST: National Institute of Standards and Technology

REVISION HISTORY

#	Revision Date	Updated By	Reviewed By	Description of Change
---	None	---	---	---
---	---	---	---	---
---	---	---	---	---

ANNEX A - TM-30 CALCULATIONS

REPORT NO. 104349704CHI-039

Test Configuration	Tested Model No.	Pass/Fail/NA
1	ESSF0606P48150930FW1	NA

TM-30 REPORT







ANSI/IES TM-30-18 Color Rendition Report

Source: User SPD

Manufacturer: Generation Brands, LLC

Date: 11/3/2020

Model: ESSF0606P48150930FW1



Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

x 0.4354
 y 0.4017
 u' 0.2506
 v' 0.5202

Colors are for visual orientation purposes only. Created with the IES TM-30-18 Calculator Version 2.00.