

GENERATION BRANDS, LLC TEST REPORT

SCOPE OF WORK

LED Performance Testing

MODEL NUMBER

ESSF0606P48600930AW1

PROJECT NUMBER

G104349704

REPORT NUMBER

104349704CHI-044

ISSUE DATE

11/16/2020

REVISED DATE

None

TEST DATES

11/03/2020 through 11/05/2020.

DOCUMENT CONTROL NUMBER

RTTDS-R-AMER-Test-3407

© 2017 INTERTEK



REPORT NUMBER

104349704CHI-044

MODEL NUMBER(s)

ESSF0606P48600930AW1

REPORT RENDERED TO:

GENERATION BRANDS, LLC
7400 LINDER AVE
SKOKIE, IL 60077
USA

STATEMENT OF LIMITATION

NVLAP Lab Code 600186-0. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

AUTHORIZATION

The testing performed was authorized by signed quote number Qu-01080748-3.

TEST STANDARDS

IESNA LM-79 - 2008: Electrical and Photometric Measurements of Solid State Lighting

ANSI NEMA ANSLG C78.377: 2017: Specifications for the Chromaticity of Solid State Lighting (SSL) Products

In Charge of Testing:



Ian Smith
Engineer
Lighting Division

Reviewer:



Jeff Davis
NA Technical Lead
Lighting Division

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

SAMPLE INFORMATION

REPORT NO. 104349704CHI-044

ITEMS RECEIVED

Item No.	Control No.	Model No.	Description	Type	Received
1	AH10292020032135	ESSF0606P48600930AW 1	ESSENCE 0606 P 800 930 WW	Production	10/29/2020

TESTED SAMPLE CONFIGURATIONS

Config No.	Tested Model No.	Item Nos. Utilized
1	ESSF0606P48600930AW1	1

SUMMARY

REPORT NO. 104349704CHI-044

PRODUCT INFORMATION AND SUMMARY OF DATA

Product Model No.:	ESSF0606P48600930AW1
Product Description:	ESSENCE 0606 P 800 930 WW
LED Model No.:	P Series 800lm/ft
Light Source:	LED

Criteria	Results	
	Goniophotometer	Integrating Sphere
Light Output (lumens)	1937.9	1981.9
Input Power (W) @ 24 (Vdc)	28.59	29.51
Lumen Efficacy (lm/W)	67.8	67.2

Criteria	Results
Input ATHD (%) @ 24 (Vdc)	NA
Correlated Color Temperature (K)	2955
Color Rendering Index - Ra (l)	97.4
Color Rendering Index - R9 (l)	96.9
Duv (l)	-0.0021
Chromaticity Coordinate (x)	0.437
Chromaticity Coordinate (y)	0.399
Chromaticity Coordinate (u')	0.253
Chromaticity Coordinate (v')	0.519

TEST METHODS

SEASONING IN SAMPLE ORIENTATION - LED PRODUCTS

No seasoning was performed in accordance with IESNA LM-79.

INTEGRATING SPHERE TESTING

A spectroradiometer and integrating sphere were used to measure the spectral distribution for each EUT resulting in photometric and colorimetric data. Electrical measurements of the unit were measured using a power analyzer. Each EUT was operated at the rated input voltage of the system in its designated orientation. The ambient temperature was measured at a position inside the sphere and stabilization procedures to LM-79 were followed.

TYPE C GONIOPHOTOMETER DISTRIBUTION TESTING

A Type C Mirror Goniophotometer system was used to measure the luminous intensity (candela) at each angle of distribution for the EUT. Electrical measurements of the unit were measured using a power analyzer. Each EUT was operated at the rated input voltage of the system in its designated orientation. The ambient temperature was measured at a position near the EUT at equal height and stabilization procedures to LM-79 were followed.

TYPE C GONIOPHOTOMETER DISTRIBUTION TESTING

REPORT NO. 104349704CHI-044

Test Configuration	Tested Model No.	Pass/Fail/NA
1	ESSF0606P48600930AW1	NA

PHOTOMETRIC AND ELECTRICAL MEASUREMENTS (25°C +/- 1°C)


Base Orientation	Input Voltage (Vdc)	Input Current (mA)	Input Power (W)	Input Power Factor ()
Up	24.0	1191.6	28.59	NA

Light Output (lm)	Lumen Efficacy (lm/W)
1937.9	67.8

INTENSITY SUMMARY - CANDELA


Angle	0	22.5	45	67.5	90
0	655	655	655	655	655
5	640	644	651	660	671
10	633	637	646	655	665
15	622	625	633	642	652
20	605	605	614	622	632
25	582	581	590	597	606
30	554	551	560	567	575
35	520	517	526	532	539
40	483	478	486	491	499
45	441	436	442	447	454
50	398	390	396	401	407
55	350	342	346	351	357
60	300	290	294	298	304
65	247	237	240	245	250
70	190	181	186	192	196
75	134	125	132	138	143
80	79	74	83	91	94
85	32	30	42	50	54
90	0	0	0	0	0
95	0	0	0	0	0
100	0	0	0	0	0
105	0	0	0	0	0
110	0	0	0	0	0
115	0	0	0	0	0
120	0	0	0	0	0
125	0	0	0	0	0
130	0	0	0	0	0
135	0	0	0	0	0
140	0	0	0	0	0
145	0	0	0	0	0
150	0	0	0	0	0
155	0	0	0	0	0
160	0	0	0	0	0
165	0	0	0	0	0
170	0	0	0	0	0
175	0	0	0	0	0
180	0	0	0	0	0

Entire luminous intensity matrix found in .IES file



REPORT NO. 104349704CHI-044

ILLUMINANCE SUMMARY



ZONAL LUMENS

Zonal Lumen Summary					
Zone	Lumens	Luminaire	Zone	Lumens	Total
0-30	514.0	26.5%	90-100	0.0	0.0%
0-40	843.8	43.5%	100-110	0.0	0.0%
0-60	1,501.4	77.5%	110-120	0.0	0.0%
60-90	436.5	22.5%	120-130	0.0	0.0%
70-100	193.3	10.0%	130-140	0.0	0.0%
90-120	0.0	0.0%	140-150	0.0	0.0%
0-90	1,937.9	100.0%	150-160	0.0	0.0%
90-180	0.0	0.0%	160-170	0.0	0.0%
0-180	1,937.9	100.0%	170-180	0.0	0.0%

INTEGRATING SPHERE TESTING

REPORT NO. 104349704CHI-044

Test Configuration	Tested Model No.	Pass/Fail/NA
1	ESSF0606P48600930AW1	NA

PHOTOMETRIC, COLORIMETRIC, AND ELECTRICAL MEASUREMENTS (25°C +/- 1°C)


Base Orientation
Up

Input Voltage (Vdc)	Input Current (mA)	Input Power (W)	Input Power Factor ()	Input ATHD (%)
24.00	1229.5	29.51	NA	NA

Measured at 24(Vdc)

Light Output (lm)	Lumen Efficacy (lm/W)	CCT (K)	CRI - Ra ()	CRI - R9 ()
1981.9	67.2	2955	97.4	96.9

Duv ()	1931 Chrom (x)	1931 Chrom (y)	1976 Chrom (u')	1976 Chrom (v')
-0.0021	0.437	0.399	0.253	0.519




REPORT NO. 104349704CHI-044

SPECTRAL DISTRIBUTION OVER WAVELENGTHS

nm	mW/nm		nm	mW/nm		nm	mW/nm		nm	mW/nm
350	0.2		460	13.0		570	27.7		680	27.8
355	0.3		465	11.4		575	28.1		685	25.2
360	0.3		470	9.0		580	28.9		690	22.6
365	0.3		475	8.5		585	29.9		695	20.2
370	0.2		480	9.2		590	31.0		700	18.0
375	0.3		485	10.1		595	32.5		705	16.0
380	0.2		490	11.6		600	34.3		710	14.0
385	0.2		495	13.5		605	36.1		715	12.2
390	0.2		500	15.4		610	37.8		720	10.6
395	0.1		505	17.0		615	39.6		725	9.1
400	0.2		510	18.5		620	41.2		730	7.9
405	0.2		515	19.8		625	42.5		735	6.8
410	0.3		520	20.8		630	43.3		740	5.9
415	0.6		525	22.0		635	43.6		745	5.0
420	1.1		530	22.9		640	43.5		750	4.4
425	1.9		535	23.7		645	42.7		755	3.7
430	3.5		540	24.6		650	41.5		760	3.2
435	5.9		545	25.4		655	40.0		765	2.7
440	11.1		550	25.9		660	37.9		770	2.2
445	19.3		555	26.4		665	35.6		775	1.9
450	21.5		560	26.9		670	33.0		780	1.7
455	15.5		565	27.3		675	30.5		---	---

Without correction of sample absorption.



Portrayed color in graphic is estimated by wavelength (nm) and may not be exact - it is a visual representation only

EQUIPMENT LIST

REPORT NO. 104349704CHI-044

#	Equipment	Model No	Control No.	Last Cal	Cal Due
1	Yokogawa Power Meter	WT210	146919	7/1/2020	7/1/2021
2	Omega Thermometer	DPI8-C24	146920	10/1/2020	10/1/2021
3	LSI High Speed Mirror Goniometer	6440T	146928	VBV	VBV
4	Newport Thermohygrometer	iServer	146957	12/2/2019	12/2/2020
5	Sorenson DC Power Supply	XHR 150-7	146922	VBV	VBV
6	Labsphere Spectroradiometer	CDS-600	146923	VBV	VBV
7	2M Rotating Sphere	7660-ROT	146923	VBV	VBV
8	Omega thermometer	USB TC08	EQA002615	4/7/2020	4/7/2021
9	Ametek DC Power Supply	XFR150-8	1468464	VBV	VBV
10	Yokogawa Power Meter	WT210	146880	10/1/2020	10/1/2021
11	Chroma Power Supply	61604	CHI0371	VBV	VBV
12					
13					
14					
15					
16					
17					
18					
19					
20					
21					
22					
23					
24					
25					
26					
27					
28					
29					
30					

Note: Standard sources listed above are traceable to NIST: National Institute of Standards and Technology

REVISION HISTORY

#	Revision Date	Updated By	Reviewed By	Description of Change
---	None	---	---	---
---	---	---	---	---
---	---	---	---	---

ANNEX A - TM-30 CALCULATIONS

REPORT NO. 104349704CHI-044

Test Configuration	Tested Model No.	Pass/Fail/NA
1	ESSF0606P48600930AW1	NA

TM-30 REPORT







ANSI/IES TM-30-18 Color Rendition Report

Source: User SPD

Manufacturer: Generation Brands, LLC

Date: 11/3/2020

Model: ESSF0606P48600930AW1



Notes: This is a recommended method for displaying ANSI/IES TM-30-18 information.

x 0.4370
 y 0.3988
 u' 0.2529
 v' 0.5193

Colors are for visual orientation purposes only. Created with the IES TM-30-18 Calculator Version 2.00.