

VISUAL COMFORT AND COMPANY TEST REPORT

SCOPE OF WORK

LED Performance Testing

MODEL NUMBER

ESSF0606P48179301WF1LEB

PROJECT NUMBER

G104941221

REPORT NUMBER

104941221CHI-038

ISSUE DATE

6/29/2022

REVISED DATE

None

TEST DATES

2022-06-29.

DOCUMENT CONTROL NUMBER

RTTDS-R-AMER-Test-3407

© 2017 INTERTEK



REPORT NUMBER

104941221CHI-038

MODEL NUMBER(s)

ESSF0606P48179301WF1LEB

REPORT RENDERED TO:

VISUAL COMFORT AND COMPANY
7400 LINDER AVE
SKOKIE, IL 60077
USA

STATEMENT OF LIMITATION

NVLAP Lab Code 600186-0. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

AUTHORIZATION

The testing performed was authorized by signed quote number Qu-01236637-1.

TEST STANDARDS

IESNA LM-79 - 2008: Electrical and Photometric Measurements of Solid State Lighting

In Charge of Testing:



Nick Lau
Engineer
Lighting Division

Reviewer:



Jeff Davis
N.A. Technical Lead
Lighting Division

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

SAMPLE INFORMATION

REPORT NO. 104941221CHI-038


ITEMS RECEIVED

Item No.	Control No.	Model No.	Description	Type	Received
1	AH06132022110621	ESSF0606P48179301WF1LEB	Surface 0606 Wall Wash D Series 350lm/ft	Prototype	6/13/2022

TESTED SAMPLE CONFIGURATIONS

Config No.	Tested Model No.	Item Nos. Utilized
1	ESSF0606P48179301WF1LEB	1

SAMPLE PHOTOS - TESTED CONFIGURATIONS



SUMMARY

REPORT NO. 104941221CHI-038

PRODUCT INFORMATION AND SUMMARY OF DATA

Product Model No.:	ESSF0606P48179301WF1LEB
Product Description:	Surface 0606 Wall Wash D Series 350lm/ft
LED Model No.:	AA5509-01
Driver Model No.:	NA
Light Source:	LED

Criteria	Results
Light Output (lumens)	1002.5
Input Power (W) @ 24 (Vdc)	14.99
Lumen Efficacy (lm/W)	66.9
Input Power Factor () @ 24 (Vdc)	NA

TEST METHODS

SEASONING IN SAMPLE ORIENTATION - LED PRODUCTS

No seasoning was performed in accordance with IESNA LM-79.

TYPE C GONIOPHOTOMETER DISTRIBUTION TESTING

A Type C Mirror Goniophotometer system was used to measure the luminous intensity (candela) at each angle of distribution for the EUT. Electrical measurements of the unit were measured using a power analyzer. Each EUT was operated at the rated input voltage of the system in its designated orientation. The ambient temperature was measured at a position near the EUT at equal height and stabilization procedures to LM-79 were followed.

TYPE C GONIOPHOTOMETER DISTRIBUTION TESTING

REPORT NO. 104941221CHI-038

Test Configuration	Tested Model No.	Pass/Fail/NA
1	ESSF0606P48179301WF1LEB	NA

PHOTOMETRIC AND ELECTRICAL MEASUREMENTS (25°C +/- 1°C)


Base Orientation	Input Voltage (Vdc)	Input Current (mA)	Input Power (W)	Input Power Factor ()
Up	23.99	624.7	14.99	NA

Light Output (lm)	Lumen Efficacy (lm/W)
1002.5	66.9

INTENSITY SUMMARY - CANDELA


Angle	0	22.5	45	67.5	90
0	432.2	432.2	432.2	432.2	432.2
5	401.8	392.7	396.5	407.8	425.4
10	357.4	351.4	362.0	383.5	416.0
15	319.0	314.4	327.7	355.9	401.0
20	288.9	283.7	296.0	326.2	380.5
25	267.1	260.9	268.2	295.8	354.8
30	251.1	243.4	244.9	265.5	325.6
35	232.7	225.9	224.8	237.0	293.5
40	209.9	203.9	205.3	210.2	259.6
45	189.6	182.5	183.2	185.4	225.7
50	170.3	162.7	160.0	161.7	192.5
55	149.7	142.8	138.0	138.3	160.0
60	128.6	122.1	116.2	114.5	129.5
65	104.9	100.0	94.3	90.9	100.6
70	80.4	77.5	73.0	68.7	74.0
75	57.9	55.1	52.2	47.4	49.6
80	36.8	34.9	32.7	28.1	27.5
85	20.9	19.0	16.2	11.8	9.7
90	0	0	0	0	0
95	0	0	0	0	0
100	0	0	0	0	0
105	0	0	0	0	0
110	0	0	0	0	0
115	0	0	0	0	0
120	0	0	0	0	0
125	0	0	0	0	0
130	0	0	0	0	0
135	0	0	0	0	0
140	0	0	0	0	0
145	0	0	0	0	0
150	0	0	0	0	0
155	0	0	0	0	0
160	0	0	0	0	0
165	0	0	0	0	0
170	0	0	0	0	0
175	0	0	0	0	0
180	0	0	0	0	0

Entire luminous intensity matrix found in .IES file



REPORT NO. 104941221CHI-038

ILLUMINANCE SUMMARY



ZONAL LUMENS

Zonal Lumen Summary					
Zone	Lumens	Luminaire	Zone	Lumens	Total
0-30	320.8	32.0%	0-10	40.7	4.1%
0-40	506.5	50.5%	10-20	114.5	11.4%
0-60	828.5	82.6%	20-30	165.6	16.5%
60-90	174.0	17.4%	30-40	185.6	18.5%
70-100	71.4	7.1%	40-50	176.0	17.6%
90-120	0.0	0.0%	50-60	146.1	14.6%
0-90	1,002.5	100.0%	60-70	102.6	10.2%
90-180	0.0	0.0%	70-80	55.4	5.5%
0-180	1,002.5	100.0%	80-90	16.0	1.6%
			90-100	0.0	0.0%
			100-110	0.0	0.0%
			110-120	0.0	0.0%
			120-130	0.0	0.0%
			130-140	0.0	0.0%
			140-150	0.0	0.0%
			150-160	0.0	0.0%
			160-170	0.0	0.0%
			170-180	0.0	0.0%

EQUIPMENT LIST

REPORT NO. 104941221CHI-038

#	Equipment	Model No	Control No.	Last Cal	Cal Due
1	Yokogawa Power Meter	WT310E	CHI0664	3/30/2022	3/30/2023
2	Omega Thermometer	DPI8-C24	146920	10/4/2021	10/4/2022
3	LSI High Speed Mirror Goniometer	6440T	146928	VBU	VBU
4	Newport Thermohygrometer	iServer	CHI0452	2/3/2022	2/3/2023
5	DC Power Supply	GENH150-5	CHI0607	VBU	VBU

Note: Standard sources listed above are traceable to NIST: National Institute of Standards and Technology

REVISION HISTORY

#	Revision Date	Updated By	Reviewed By	Description of Change
---	None	---	---	---
---	---	---	---	---
---	---	---	---	---